



**DC-AC Inverter**  
**⚡ Pure Sine Wave**

**Model**  
**PST-600-48**  
**48 VDC - 120 VAC**

### Design Features

- High efficiency
- 166% Surge Power
- Temperature controlled cooling fan – reduces energy consumption
- Low RF emissions
- Wide operating DC input range: 42.0 - 64.0 VDC
- Commercial grade design suitable for heavy duty loads, long periods of continuous operation & for emergency back up
- UPC – Universal Protection Circuit: low voltage, over voltage, over temperature, over load and short circuit.
- Low idle power draw
- Duplex GFCI protected AC outlets
- Optional remote control (sold separately): Model RC-15A
- Meets UL & CSA Standards, FCC compliant

**2 YEAR LIMITED WARRANTY**



		<b>MODEL NO.</b>	<b>PST-600-48</b>
<b>OUTPUT</b>		OUTPUT VOLTAGE	120 VAC ± 3%
		MAXIMUM OUTPUT CURRENT	5.1A
		OUTPUT FREQUENCY	60 Hz ± 1%
		TYPE OF OUTPUT WAVEFORM	Pure Sine Wave
		TOTAL HARMONIC DISTORTION OF OUTPUT WAVEFORM	< 3%
		CONTINUOUS OUTPUT POWER (At Power Factor = 1)	600 Watts
		SURGE OUTPUT POWER	1000 Watts (< 8 ms)
		PEAK EFFICIENCY	90%
		AC OUTPUT CONNECTIONS	NEMA5-20R GFCI Duplex Receptacle
<b>INPUT</b>		NOMINAL DC INPUT VOLTAGE	48 VDC
		DC INPUT VOLTAGE RANGE	42.0 - 64.0 VDC
		MAXIMUM INPUT CURRENT	20A
		DC INPUT CURRENT AT NO LOAD	< 0.3A
		DC INPUT CONNECTIONS	Bolt & Nut: 5/16" x 18 TPI
		DC INPUT FUSES (INTERNAL)	2 x 10A = 20A (Each 10A, 58V, Blade Type)
<b>DISPLAY</b>		LED	Power, Overload, Over Temperature
<b>PROTECTIONS</b>		LOW DC INPUT VOLTAGE ALARM	42.0V ± 0.5V
		LOW DC INPUT VOLTAGE SHUTDOWN	40.0 ± 0.5 VDC ; Auto-reset: 46.0 ± 0.5 VDC
		HIGH DC INPUT VOLTAGE SHUTDOWN	64.0 VDC ; Auto-reset: < 64.0 VDC
		SHORT CIRCUIT SHUTDOWN	When output voltage drops to 80 VAC or lower for 1 to 1.5 sec
		OVERLOAD SHUTDOWN	At overload of 110% to 115% for 2 to 2.5 sec
		GROUND FAULT SHUTDOWN	Through GFCI outlets (5 to 6 mA leakage)
		OVER TEMPERATURE SHUTDOWN	90°C ± 5°C (Sensed at internal hot spot) ; Auto reset at 65°C ± 5°C
	REVERSE POLARITY ON DC INPUT SIDE	External / internal DC sides fuses will blow	
<b>REMOTE</b>		WIRED REMOTE CONTROL WITH LED DISPLAY	RC-15A with 5m / 16.5 ft cable (sold separately)
<b>COOLING</b>		FORCED AIR COOLING	1 Temperature controlled fan (Temperature is sensed at internal hot spot ; Fan ON at 55°C ± 3°C ; Fan OFF at 45°C ± 3°C)
<b>COMPLIANCE</b>		SAFETY	Meets UL Standard UL 60950-1 and CSA Standard C22-2 No.107.1-01 for Information Technology Equipment
		EMI / EMC	FCC Part 15(B), Class B
<b>ENVIRONMENT</b>		OPERATING TEMPERATURE RANGE	-20°C to 40°C / -4°F to 104°F
<b>DIMENSIONS</b>		(W X D X H), MM	238 x 276.2 x 82
		(W X D X H), INCHES	9.37 x 10.87 x 3.23
<b>WEIGHT</b>		KG / LBS	7.1 / 15.6

**NOTES:**

1. All power ratings are specified for resistive load at Power Factor = 1.
2. All specifications given above are at ambient temperature of 25°C / 77°F.
3. Specifications are subject to change without notice

12001-PST-600-48-1016